Index

A

Aborting a connection 4.5
AppleTalk and EtherTalk 4.7, 8.2, 8.4, 8.13
ARPANET 8.10
ASCII
    encoding 7.4
    file 5.1
    transfer mode 5.4

B

Backspace command 3.7
BACKSPACE key function 2.2, 3.2, 3.6, 4.1
Binary file 5.1
    transfer 5.7

C

Clear screen
    Tektronix character
    sequence (ESC, FF) 6.1
    Saves Lines command 3.8
Client 5.1
Clipboard 6.3
Close Connection
    command 1.3
    dialog box 1.3
Color
    applying to session windows and fonts 3.11-3.12
    color selection dialog box 3.12
    color wheel dialog box 3.12
    command 3.11
    maps (ICR) 7.6
Columns 3.2
Command key equivalents for menu commands 2.1
Compatibility limitations 8.16
Configuration
    assigning an Internet number (NCSA Version) 8.2
    configure Network Parameters dialog boxes 8.2
    configuring network parameters 8.1
    converting UNIX /etc/ hosts files 8.12, Appendix B
    domain name lookup 8.14
    dynamic IP addressing 8.3
    dynamic IP codes 8.4
    entering parameters 8.6-8.8
    file 8.5
    hardware xii
    internet subnetting 8.4
    password protection 8.15
    static IP numbers 8.3

2
Configuration dialog box 3.2
Backspace Is 3.2
Columns 3.2
Echo Mode 3.3
Return Sends 3.3
Scrollback 3.4
Tek Clear Screen 3.3
Window Name 3.2
Configuration file
editing 8.5
entering parameters 8.6-8.8
entry syntax 8.5
nameserver entry 8.14
placing 8.5
Configure Network
command 4.7, 8.1
dialog box 4.8
Config.tel
entering parameters 8.6-8.8
entry syntax 8.5
placing 8.5
Connection
aborting attempts at 4.5
closing 1.3
multiple connections 4.3
opening 1.1
status dialog box 4.5
Connections menu 1.2, 4.4
meanings of symbols 4.4
Copy
commands 1.4
procedure 1.4
graphics windows (ICR) 7.6,
(Tektronix) 6.3
Copy Table
command 1.4
threshold 3.5
Croft gateway software 8.3
Customizing Telnet 4.1
Cut
command 1.4
procedure 1.4

D

Delete command 3.7
DELETE key function 2.2, 3.2, 3.7
Domain name lookup
default domain 8.15
domain search order 8.14
Dynamic IP addressing 8.3-8.4
administered (Croft) 8.3
AppleTalk-based (Croft or
Kinetics) 8.4
dynamic IP codes 8.4
RARP (EtherTalk) 8.3
sample assignment 8.4

E
Echo mode 3.3
Encoding
    ASCII 7.4
    run-length 7.5
Erase character 4.7
Erase line 4.7
Ethertalk and AppleTalk 8.13
Exiting NCSA Telnet 1.5

F
File transfer 5.1
    about FTP 5.2
    changing the default directory 5.5
    commands 5.4
    cursor 5.3
    FTP log 5.4
    of MacBinary files 5.7
    of multiple files 5.6
    setting the transfer mode 5.4
    to the Host 5.6
    to the Macintosh 5.5
Finder 4.2
Font
    choices 3.10
    color 3.11
    command 3.10
    size 3.11, 4.2
FTP
    about 8.16
    commands 5.2, 5.4
    log 5.4
    password protection 8.15
FTP Enable command 5.2

G
Get command 5.4, 5.7
Graphics windows (Tektronix)
    clearing 6.1
    deleting 6.2
    detaching 6.1
    printing 6.3
    zooming/unzooming 6.2
Graphics windows (ICR)
    color problems 7.6
    copying 7.6
    memory allocation 7.6

H
Half duplex 3.3
Hardware
    AppleTalk and EtherTalk 8.13
    combined network drivers 8.13
    requirements xi-xii

I
ICMP Redirects 8.16

ICR
about 7.1
commands and command parameters 7.2-7.4
description of protocol 7.2
sample C program 7.7
Imcomp 7.2, 7.4
Internet subnetting 8.4
Internet address
assigning 8.2-8.4
entering 5.3
viewing 4.7
Interrupt Process 4.6
IP number
assigning 8.2-8.4
dynamic addressing 8.3
entering 5.3
static 8.3
viewing 4.7
Interactive Color Raster Graphics 7.1
color maps 7.6
description of the protocol 7.2
example program for ICR in C 7.7
ICR commands 7.2
using the ICR protocol 7.2

J
Jump Scroll Command 3.8

K
Keyboard commands 2.1
Kinetics gateway software 8.2

L
Load Set command 4.2
Local Echo command 3.7
Local echo mode 3.3
Logging in to your host 1.2

M
MacBinary
command 5.7
files 5.7
Reset MacBinary for each FTP 5.7
transferring MacBinary files 5.7
MacBinary Enabled command 5.7
Macros
common key combinations 2.9
defining macros 2.8
dialog box 2.9
entering key sequences 2.9
reverting to the previous definitions 2.9
set window size 3.9
MacTCP drivers
transition to 8.1
MacTCP version of NCSA Telnet 8.1
Memory allocation 7.6
maxset 8.14

mtu 8.14
Multifinder 7.6, 8.1, 8.7

N
NCSA version of NCSA Telnet 8.1
Network configuration xii
Network parameters
    configuring 8.1
    dialog boxes 8.2
Network-related commands 4.7

O
Open Connection
    command 1.1
    dialog box 1.1

P
Page Setup command 1.4, 6.3
Paste
    command 1.4
    procedure 1.4
Password
    file 8.15
    FTP password protection 8.15
Paste command 1.4
Performance tuning 8.14
Ping 8.15
Preferences
    command 2.1
    dialog box 2.2
Preferences command 2.1
Preferences dialog box 2.2
    Command keys 3.5
    Copy Table Threshold 3.5
    MacBinary 3.6
    Remap backquote to ESCape 3.6
    Remap option key to control 3.5
    Reset MacBinary for each FTP 3.6
    Windows don’t go away on close 3.6
Print
    command 1.4
    procedure 1.4
    graphics windows (Tektronix) 6.3
Print Selection command 1.4
Put command 5.4, 5.4

Q
Quit command 1.5

R
RARP 8.3
Reset Terminal command 4.8
resume 4.2, 4.7
rwin 8.14

S
Save Set command 4.1, 4.2

Scrollback 3.3, 4.2
Send “Abort Output” command 4.6
Send “Are You There?” command 4.6
Send “Erase Character” command 4.7
Send “Erase Line” command 4.7
Send FTP Command 5.3
Send “Interrupt Process” command 4.6
Send IP number 5.3
Server 5.1
Session menu
    Backspace 3.7
    Clear Screen Saves Lines 3.8
    Color 3.11
    Delete 3.7
    Font 3.10
    Jump Scroll 3.8
    Local Echo 3.7
    Reset Terminal 3.8
    Set Usable Lines 3.8
    Setup Keys 3.10
    Size 3.11
    TEK Page 3.8
    Wrap Mode 3.7
Session names
    rules for 4.3
Session window
    increasing or decreasing the number of lines in 3.8-3.10
Set
    icon 4.2
    saving 4.1
    using 4.2
Set Macros command 2.8
Set Transfer Directory command 5.5
Setup Keys 2.6
    command 2.6
    dialog box 2.7
Set Usable Lines command 3.8
Show FTP Log command 5.4
Show Network Numbers command 4.7
Size command 3.11
Static IP numbers 8.3
Suspend Network command 4.2, 4.7

T
Table 1.4, 3.5
TCP/IP 8.1, 8.13
TEK Page command 6.1
Tektronix graphics 6.1
Telnet
    standard protocol 8.16
Telnet options 2.6, 4.5
    changing key assignments for 2.6
    Interrupt 2.7
    Resume 2.8
    Send “Abort Output” 4.6
    Send “Are You There?” 4.6
    Send “Erase Character” 4.7

Send “Erase Line” 4.7
Send “Interrupt Process” 4.6
Suspend 2.8
Telpass 8.15
Terminal type
setting a 1.3
Timing mark operation 2.7
Trailers 8.16

U
UNIX /etc/hosts files 8.12, Appendix B

V
VT102
CAN characters (dec 24) and 6.2
emulation 1.3, 2.5-2.6, 8.15
equivalent keystrokes 2.6
reset terminal 4.8
terminal wrap 8.11

W
Wild card feature 5.7
Window name 4.4
Wrap Mode command 3.7