METAFONT for Beginners

Geoffrey Tobin

ecsgrt@luxor.latrobe.edu.au

Scope

This is not a tutorial on METAFONT.[1] It is an attempt to describe how some of the pitfalls in running the program may, hopefully, be avoided.

It is a common experience to have initial (and medial and final) difficulty with running METAFONT, and not all 'TEXnicians' are as familiar with METAFONT as they are with TEX. Still, nothing ventured, nothing gained. So let's be of good cheer, and get down to work.

1 What is Metafont?

METAFONT is a program for making bitmap fonts for use by TEX, its viewers, printer drivers, and related programs. It interprets a drawing language with a syntax apparently derived in part from the Algol family of programming languages, of which C, C++, Pascal and Modula-2 are members.

The input can be interactive, or from a source file. METAFONT source files are usually suffixed '`.mf`'.

METAFONT sources can utilize scaling, rotation, reflection, skewing and shifting, and other complex transformations in obvious and intuitive ways. But that is another story, told (in part) by *The* METAFONT*book*.

METAFONT's bitmap output is a GF (*generic font*) file. This may be compressed to an equivalent PK (*packed*) font by the auxiliary program *GFtoPK*.

Why doesn't METAFONT output PK fonts directly? Firstly, Tomas ROKICKI had not invented PK at the time Donald Knuth was writing METAFONT. Secondly, to change METAFONT now would be too big a change in Knuth's opinion. (Knuth is a very conservative programmer; this fact is a two-sided coin.)

GF and PK files are suffixed '`.*gf`' and '`.*pk`' respectively, where, in a typical UNIX installation, the '`*`' stands for the font resolution. (Resolution will be explained below.) MS-DOS truncates file name suffixes to three characters, so a font suffix '`.1200gf`' becomes '`.120`' — beware of this!

A bitmap is all that's needed for large-scale *proofs*, as produced by the *GFtoDVI* utility, but for TEX to typeset a font it needs a TFM (*TEX Font Metric*) file to describe the dimensions, ligatures and kerns of the font. METAFONT can be told to make a TFM file, by making the internal variable '`fontmaking`' positive. Most output device modes (see below) do this.

Remember that TEX reads only the TFM files. The *glyphs*, or forms of the characters, as stored in GF or PK font files, do not enter the picture (I mean, are not read) until the DVI drivers are run.

TEX can scale TFM files. Unfortunately, bitmaps such as GF and PK are not scalable. However, METAFONT files can be compiled into fonts of arbitrary scale by METAFONT, even by non-programmers.

Incidentally, properly constructed TFM files are device-independent, so running METAFONT with different modes normally produces the identical TFM. Dimensions in TFM files are specified to METAFONT in device independent 'sharped' dimensions (commonly suffixed by #), where a value of 1 corresponds to the dimension of `1pt` (typographical point). Most of METAFONT's calculations are done with (resolution and device dependent) pixels as units. Care must be taken by font designers to *always* calculate unsharped dimensions from sharped ones, and never the other way round, so as to keep roundoff errors or similar effects from influencing the TFM files to depend on resolution or device. Although type quality will be influenced only in minuscule ways, this is one of the more common reasons for checksum errors reported by printer drivers. Note that the only way to be sure that a TFM file is device-independent is to create the font in different modes and compare the resulting TFM's, perhaps using *tftopl*.

More detailed descriptions of TFM and GF files, and of *proof* mode, are found in Appendices F, G, and H, respectively of *The* METAFONT*book*.

2 Getting Metafont's Attention

2.1 Typing at METAFONT's '**' prompt

If you type the name of the METAFONT program alone on the command line:

```
mf
```

then `mf` displays a '`**`' prompt, which 'is METAFONT's way of asking you for an input file name'. (See

[1] This article is a trimmed version of the tutorial file made available on TEX archives; a current full version can be obtained from the *documentation* directory on any CTAN archive (see elsewhere in this issuefor more details of CTAN).

The METAFONT*book*, Chapter 5: 'Running METAFONT'.) Thus, to process a METAFONT file named `fred.mf`, you may type:

```
fred
```

A backslash ('\') can also be typed here. This causes all subsequent commands at the prompt line to be interpreted as in a METAFONT file. (Concerning the backslash, see *The* METAFONT*book*, Chapter 20: 'More About Macros', pages 179 and 180 in the 1986 edition.) Thus we can respond to the ** prompt with:

```
\ input fred
```

or even:

```
\ ; input fred
```

The backslash is useful because certain commands are often executed before a METAFONT file is input. In particular, quality printing requires the METAFONT command `mode`, and output magnification employs the `mag` command. For example:

```
\mode=localfont; mag=magstep(1);
                            input fred
```

To read MS-DOS pathnames at the ** prompt, this satisfies METAFONT:

```
\ input \seldom\fred.mf
```

as does:

```
d:\seldom\fred.mf
```

2.2 Typing on the Command Line

Most METAFONT implementations permit you to type METAFONT commands on the command line, instead of at the ** prompt. (Rather, it is automatically passed to that prompt.)

On MS-DOS, type commands as at the ** prompt:

```
mf \mode=localfont; input myfont10
```

On UNIX, command shells typically interpret semicolons, backslashes and parentheses specially, unless they are 'quoted'. So, when typing those characters as part of instructions to METAFONT on the UNIX command line, it is wise to accustom yourself to protecting them with *apostrophes*:

```
mf '\mode=localfont; input myfont10'
```

If `localfont` makes fonts for a 300 dots per inch (dpi) device, this should produce a TFM file, '`myfont10.tfm`', and a 300 dpi GF font file, '`myfont10.300gf`'. Almost all of the following will presume a 300 dpi device, and other resolution devices will have appropriately different font file names.

These command lines are a bit long, very often used, and rather intolerant of mistakes so you might type the repetitive parts into a UNIX shell script or an MS-DOS batch file, as appropriate.

In UNIX, the ** prompt has the advantage that those pesky apostrophes are not needed. (Indeed, those apostrophes are always wrong at the ** prompt — METAFONT doesn't understand them. It would not understand them on the command line either—it is just that the shell does not hand them over to METAFONT.) However, for shell scripts (and for batch files in MS-DOS), the command line is a boon.

2.3 'Please type another input file name: '

When METAFONT cannot find the main source file, it doesn't quit. For example, when I typed `mf fred`, METAFONT said:

```
This is METAFONT ...
**fred
! I can't find file `fred.mf'.
<*> fred

Please type another input file name:
```

The usual program interrupts (eg, Control-C) don't work here, and the '`Please type ...`' prompt does not understand METAFONT commands: it will read only the first word, and insist on interpreting this as a file name.

Beginners faced with this often wonder how to avoid an endless loop or a reboot, or try to think of a METAFONT file that they do have in METAFONT's path. In the latter case, the canonical name to use is '`null`', standing for the file '`null.mf`'.

In fact, the solution is much easier: on the systems that I have tried, a simple end of file marker ('control-Z' in MS-DOS, 'control-D' in UNIX) stops METAFONT in its tracks:

```
! Emergency stop.
<*> fred

End of file on the terminal!
```

3 Base files

In versions 2.7 and 2.71, the METAFONT language contains 224 (previous versions had fewer) primitives, which are the commands preceded by an asterisk in the Index (Appendix I) to *The* METAFONT*book*. From these we can build more complex operations, using macros. In METAFONT macros have some of the desirable characteristics of functions in other languages. Collections of macros can be stored in METAFONT source files.

Base files are *precompiled internal tables* that METAFONT loads faster than it loads the original METAFONT source files. Thus, they are closely analogous to TEX's *format* files.

3.1 The plain base

The `plain` base provides the commands that *The* METAFONT*book* describes. (See Appendix B of *The* METAFONT*book*, if you have it around — maybe a library has it — I'm learning from a copy borrowed from the local university's library.)

When it starts, METAFONT automatically loads[2] the `plain` base. This is usually called `plain.base`, or sometimes only `mf.base`, although for those systems concerned (such as UNIX), both file names should really be present.

EmTEX for MS-DOS calls the plain base `plain.bas`, due to filename truncation.

3.2 Loading a Different Base

Suppose that you have a base named `joe.base`. Typing

```
mf &joe
```

or (on unix, where we must either quote or escape the ampersand)

```
mf \&joe
```

or responding

```
&joe
```

to the `**` prompt, omits loading `plain` base, and loads the `joe` base instead. Typically, however, the `joe.mf` file which originally produced the `joe` base will have included `plain.mf`, because working without the `plain` base macros would be too cumbersome. (Refer to *The* METAFONT*book* (1986), Chapter 5: 'Running METAFONT', page 35, 'dangerous bend' number two.)

The '`cm`' base, for making the Computer Modern fonts, can be loaded in that way:

```
mf &cm
```

Remember to quote the ampersand under UNIX!

3.3 The Linkage Trick

On systems such as UNIX where programs can read their own command line name, and where files may be linked to two or more names, then programs can modify their behavior according to the name by which they are called. Many UNIX TEX and METAFONT installations exploit this in order to load different *format* and *base* files, one for each of the various names to which TEX and METAFONT are linked. Such installations can often be recognized by the presence of the executable '`virmf`' in one of the directories in the `PATH`.

For example, if a base file called '`third.base`' resides where METAFONT can find it, then `virmf` can be linked to `third`. In UNIX, a *hard link* is formed by

```
ln virmf third
```

On systems supporting *symbolic links*, you should make all of these links symbolic, rather than hard, or else you will have to redo them every time you install a new copy of `virmf`; see below. In UNIX, this is done by

```
ln -s virmf third
```

Normally one wants `mf` to load the `plain` base, so in such installations one links `plain.base` to `mf.base`:

```
ln plain.base mf.base
```

Again, you'd best make that link symbolic. This comment applies for the rest of this section as well.

As another example, take the '`cm`' base. In *web2c*:

```
ln virmf cmmf
ln cm.base cmmf.base
```

so that '`cmmf`' automatically loads '`cm.base`'.

This applies equally to TEX, which is why `tex` and `latex` are then links to `virtex`, `tex.fmt` is a link to `plain.fmt`, and `latex.fmt` is a link to lplain.fmt:

```
ln virtex tex
ln plain.fmt tex.fmt

ln virtex latex
ln lplain.fmt latex.fmt
```

Karl Berry's *web2c* distribution for UNIX uses this '*linkage trick*'.

If you used symbolic links, you can laugh off the following

WARNING: This linkage is convenient, but watch out during updates! If `mf.base` is a *hard link* to `plain.base`, then replacing `plain.base` with its new version severs the link: `mf` will still load `mf.base`, but it will be the old version! The proper procedure is to remove the old `mf.base`, and relink. On UNIX:

```
rm mf.base
ln plain.base mf.base
```

On most UNIX systems, `ln -f` will automatically remove the second file (if present) — in this case, mf.base — before linking.

Alternatively, *web2c* will update '`plain.base`' (and '`plain.fmt`', and so on) for you, if you tell *web2c*'s `Makefile` to

```
make install
```

Symbolic links, on systems that have them, are probably the best method of handling updates, at least when doing them manually. (Consult your system administrator for details.)

[2] There are releases of METAFONT that contain the `plain` base, and so don't have to load it. However, on most computers, including personal computers, reading bases is so fast that such a *preloaded* base is unnecessary.

3.4 Making a Base; the Local Modes file

The `plain` base is made from a METAFONT file named `plain.mf` and, commonly, from some other file, often called `local.mf` or `modes.mf`.

The `local/modes` file lists printers (and monitors), giving each output device a font-making *mode*, containing a description of some refinements that must be made in order to produce good-looking output. For instance, how to make the characters just dark enough, and how to make diagonal lines come out sharply.

If you want to make a base, you need a variant of the METAFONT program called '`inimf`'. (See *The* METAFONT*book*, p 279.) For example, `plain.base` can be made in UNIX by typing:

```
inimf 'plain; input local; dump'
```

If using the emTEX version of METAFONT for a PC, type:

```
mf/i plain; input local; dump
```

4 Fonts

4.1 Proof Mode

The purpose of METAFONT is to make fonts. For æsthetically pleasing PK bitmaps, the correct device mode must be selected.

An obstacle to beware of is that `plain` METAFONT uses *proof* mode by default. (*The* METAFONT*book*, page 270, defines this mode.) That means writing unmagnified font files with a resolution of 2601.72 dots per inch (dpi); that's 36 pixels per point. (One point is 1/72.27 of an inch.) Proof mode does **not** produce a TFM file.

What good is proof mode, and why is it the default? *Proofs* are blown up copies of characters used by font designers to judge whether they like the results of their work. Naturally, proofs come first, and normal sized character production later — if you're a font designer.

So there are two clues that proof mode is on: font files with extensions like '`.2602gf`' (or on MS-DOS, '`.260`'), and the 'failure' to produce any TFM file.

On some systems, such as X11, a third clue is that the proof font may be drawn on the screen — it is so large, you can't miss it!

4.2 Localfont Mode

When using a stable font, or when testing the output of a new font, we *don't* want proof mode, we want our local output device's mode. Usually, METAFONT is installed with a '`localfont`' assigned in the `local/modes` file. On our department's Sun Network, we have assigned

```
localfont:=CanonCX
```

We use Karl Berry's '`modes.mf`'[3], which contains modes for many, many devices. We chose the `CanonCX` mode because '`modes.mf`' recommends it for Apple Laserwriters and HP Laserjet II printers, which we use.

To process a METAFONT source file named '`myfont10.mf`' for the most usual local device, specify the local mode to `mf` before inputting the font name:

```
\mode=localfont; input myfont10
```

This should produce a GF font file, '`myfont10.300gf`' ('`myfont10.300`' in MS-DOS), and a TFM file, '`myfont10.tfm`'.

4.3 Font Naming

By the way, if you modify an existing, say a Computer Modern (cm), font, you must give it a new name. This is an honest practice, and will avoid confusion.

4.4 Magnification (and Resolution)

Now suppose that you want `myfont10` to be magnified, say to magstep 1 (magnified by 1.2), for a 'jumbo' printer. Assuming that the `local/modes` file has a mode for the jumbo printer, you may then run METAFONT with the following three commands:

```
\mode=jumbo; mag=magstep(1);
                    input myfont10
```

to produce '`myfile10.tfm`' (again!) and a GF font, '`myfile10.360gf`'. On MS-DOS, the file names will be truncated; for example, '`myfile10.360`'.

The '`360`' is '300 * 1.2', indicating the magnification. A 360 dpi font can be used either as a magnification 1.2 font on a 300 dpi printer or as a normal sized font on a 360 dpi printer.

Note, however, that the METAFONT language includes special hints for each output device which clue METAFONT as to the reactions of the output device to pixel-sized minuscule changes.

So for highest quality, you would not even want to mix the fonts for two 300 dpi printers, unless they share the same mode and most probably the same print engine.

4.5 GFtoPK

TEX uses only the TFM file, which METAFONT will produce if it is in a font-making mode. (*The* METAFONT*book*, Appendix F.) Most DVI drivers read the PK font format, but METAFONT makes a GF (Generic Font) file. So we need also to apply the *GFtoPK* utility:

```
gftopk myfile10.300gf
```

to produce the wanted '`myfile.300pk`' (or, on MS-DOS, '`myfile.pk`') PK font.

[3] Available at `ftp.cs.umb.edu` in the `pub/tex` directory.

4.6 Storing the Fonts

Now we have the fonts, where do we store them? TEX, METAFONT and the various driver programs are compiled with default locations written in. These can be overridden by certain environment variables. The names of these variables differ between systems, but on UNIX they might, for example, be 'TEXFONTS' for the TFM files, and either 'PKFONTS' or 'TEXPKS' (or both of those) — before searching 'TEXFONTS' — for PK fonts. You can find out what environment variables you now have by typing '`set`' in MS-DOS and '`env`' in the Bourne shell, sh, in UNIX. In the UNIX C shell, `csh`, type '`setenv`'.

If you want TEX and METAFONT to find files in the current directory (as you almost certainly do!), then one way is to put '`.`' into their search paths. (Both UNIX and MS-DOS accept the `.` notation for the current directory.) Default search paths are compiled into TEX and METAFONT, but users can customise the environment variables that the programs read, to override the defaults.

METAFONT as well as the DVI drivers, can also be given full path specifications for input files.

On the other hand, you may be content with your new font, and you may have write access to the place where most of the fonts are stored. In that case, copy your font to there. There will be a place for the TFM files, and another for the PK files. It is up to you or your local system administrator(s) to know where these directories are, because their names are very locale dependent.

5 Some Limitations of Metafont

METAFONT contains some builtin limitations, some obvious, others less so.

Parts of the following list are most useful to budding programmers, though casual users may wish to read it to learn whether an error message produced by somebody else's METAFONT file is very serious or not.

1. All valid numbers are strictly less than 4096.
2. *The* METAFONT*book*, in 'Appendix F: Font Metric Information', warns of one limitation that I've met when processing some fonts.
   'At most 15 different nonzero heights, 15 different nonzero depths, and 63 different nonzero italic corrections[4] may appear in a single font. if these limits are exceeded, METAFONT will change one or more values, by as little as possible, until the restriction holds. A warning message is issued if such changes are necessary; for example
   `(some charht values had to be adjusted by as much as 0.12pt)`
   means that you had too many different nonzero heights, but METAFONT found a way to reduce the number to at most 15 by changing some of them; none of them had to be changed by more than 0.12 points. No warning is actually given unless the maximum amount of perturbation exceeds $\frac{1}{16}$ pt.'
   Every correct implementation of METAFONT will adjust character box dimensions by the same amount, giving the same TFM files, so we ignore small perturbations in other people's fonts. When designing your own fonts, however, I think it is courteous to keep within the limits, so as not to worry inexperienced users.
3. In the `addto` picture command, `withweight` only accepts values that round to `-3`, `-2`, `-1`, `+1`, `+2`, or `+3`. To obtain other pixel weights, you can apply further `addto` commands.
4. The memory size of the version of METAFONT you use is an evident, implementation dependent restriction, but it may be, as in TEX, that memory is not enough simply because, if you'll pardon my saying so, some of your coding may be seriously inefficient or logically invalid.

6 What Went Wrong?

The complexity of wrong things far exceeds that of things intended. *The* METAFONT*book*, chapter 5, 'Running METAFONT', contains instructive examples, and supposedly 'dangerous', but actually basic and useful, notes.

In that chapter, and in chapter 27, 'Recovery from Errors', Knuth discusses the diagnosis of METAFONT's error messages. I find this perhaps the hardest part of the book — if not of using METAFONT.

Incidentally, METAFONT's error messages are contained in an ASCII file called '`mf.pool`'. Reading the `pool` file can be entertaining.

6.1 Big fonts, but Unwanted

Recently, I found myself accidentally producing fonts with extensions like '`3122gf`'. How?

METAFONT *will take* **anything** *as an excuse to revert to* **proof mode**.

The '`3122`' is a magstep 1 proof mode. It is

```
(1.2)^1 * 2601.72  = 3122.164
                     dots per inch.
```

My intention was for METAFONT on a PC to use an HP Laserjet mode in place of proof mode. However, METAFONT's command line resembles the law: *every stroke of the pen is significant*. What I had forgotten was that on my setup, '`localfont`' must be explicitly requested.

EmTEX's METAFONT, with `plain.mf`, defaults to proof mode. However, I usually want a local printer's font-making mode. So to process `pics.mf` correctly, I need to say:

```
mf '\mode=localfont; input pics'
```

[4] Respectively, `charht`, `chardp` and `charic` values.

6.2 Consequences of Some Typing Errors on METAFONT's command line

Small typing errors are so common, and yet undocumented (why are common mistakes not documented?), that I thought I'd list several that have tripped me up on innumerable occasions. After all, why reinvent the car crash?

Consider a source file '`pics.mf`' that contains '`mag=1200/1000;`', so it is automatically scaled by 1.2 (ie, by magstep 1). If the target printer has 300 dpi, then a 360 dpi GF font is wanted.

Here is the gist of what happens for various typing errors, when using emTEX's '`mf186`' on a 286 PC to process '`pics.mf`'.

1. `mf186` ⟹ METAFONT will keep prompting for arguments:
   ```
   **
   ```
   We can type the contents of the command line here; for example, I can now type '`pics`'. In fact, even if you use the command line, the `.log` ('transcript') file shows METAFONT echoing its interpretation of the command line to a ** prompt.
2. `mf186 pics` ⟹ proof mode:
   ```
   ! Value is too large (5184)
   ```
   No TFM is produced, and the GF file has resolution 3122 dpi. (3121.72 dpi, to be precise.)
3. `mf186 mode=localfont; input pics` ⟹ misinterpretation:
   ```
   ! I can't find file
              'modes=localfont.mf'
   ```
   So, '`modes`' needs that backslash, otherwise METAFONT thinks it is the start of a source font's filename. Backslash ('\') and ampersand ('&') are escapes from this standard interpretation by METAFONT of the first argument. (Ampersand is in fact only a temporary escape, as METAFONT resumes the `mf` filename prompting attitude as soon as a base is read.)
4. `mf186 \mode=localfont input pics` ⟹ weird effect:
   ```
   >> unknown string mode_name1.2
   ! Not a string
   <to be read again>
                      ;
   mode_setup->
        ...ode)else:mode_name[mode]fi;
   l.6 mode_setup
                    ;
   ```
   Wow! What a difference a semicolon can make!
5. `mf186 \mode=localfont pics` ⟹ almost nothing happens:
   ```
   ** \mode=localfont pics


   *
   ```
   There's the echo I mentioned. From the lack of activity, `pics` evidently needs to be '`input`'.
6. `mf186 \mode=localfont; pics` ⟹
   Same as 5.
   So, yes, when the mode is specified, we need '`input`' before '`pics`'.
7. `mf186 &plain \mode=localfont; input pics` ⟹
   Works.
   Just as without the '`&plain`', it writes a GF file, '`pics.360gf`', which is correct. (MS-DOS truncates the name to '`pics.360`'.) So, redundancy seems okay. Does it waste time, though?

6.3 Finding the Fonts

Finding the fonts (`*.mf`, `*.tfm`, `*.gf`, and `*.pk`) trips up TEX, METAFONT, *GFtoPK* and the output drivers continually. '`pics.tfm`' needs to be put where TEX will look for TFMs, so I needed to ensure that '`.`' was in the appropriate path environment variable. Similarly for the METAFONT, GF and PK font files.

Environment variables can be tricky. For instance, emTEX's font-making automation program '*MFjob*' cannot make fonts in the current directory unless both '`.`' and '`..`' are added to `MFINPUT`. This was not documented.

Also, some popular TEX output drivers, such as the emTEX drivers on MS-DOS and OS/2, and Tomas Rokicki's '`dvips`' which has been ported to many systems, make missing fonts automatically — provided that they can find the necessary METAFONT source files. Again, making fonts in the current directory can require some tweaking.

6.4 Strange Paths

METAFONT satisfactorily fills simple closed curves, like '`O`' and '`D`', but filling a figure eight, '`8`', causes a complaint:

```
Strange path (turning number is zero)
```

because METAFONT's rules for distinguishing inside from outside might or might not give what you want for an '`8`', as there is more than one conceivable answer. You can use the 'positive turning rule' for all cases, and also turn off complaints, by setting

```
turningcheck := 0;
```

Chapter 13: 'Drawing, Filling, and Erasing', and Chapter 27: 'Recovery from Errors', discuss `strange paths` in greater depth.

Sometimes, when making a perfectly valid font, but in *low* resolutions, as for previewers (eg, VGA has 96 dpi), one may get flak about a '`Strange path`' or '`Not a cycle`' or something similar. Don't be alarmed. Fonts for previewing will still be OK even if not perfect.

Consequently, it is an idea to make low resolution fonts in METAFONT's `nonstopmode`.

Examples of fonts that give messages of this nature are the pleasant Pandora, and — from memory —

the commendable Ralf Smith's Formal Script (`rsfs`). Everything is fine at higher resolutions.

Mind you, some fonts provoke sporadic (that is, design size dependent) strange path messages at 300 dpi (photo-typesetter users would consider that low resolution), yet the printed appearance showed no visible defect.

Why do strange paths occur? One cause is rounding error on relatively coarse grids.

To summarize, if your viewed or printed bitmaps are fine, then you are OK.

7 Metafont Mail List

Since 10 December 1992, there has been an e-mail discussion list for METAFONT, created:

1. as a means of communication between hooked METAFONTers;
2. as a way to bring the 'rest of us' closer to them;
3. as a means to get quick and efficient answers to questions such as:
   - why do I always get a '.2602gf' file?
   - what is a 'strange path', and what can I do to avoid it?
   - is there a way to go from METAFONT to PostScript and vice-versa?
   - where can I find a Stempel Garamond font written in METAFONT?
   - what is metaness?
4. and finally, as a first step to encourage people to undertake METAFONTing, and start a new post-Computer Modern era of METAFONT!

To subscribe to this list, send the following two lines to `listserv@ens.fr` on the Internet:

```
SUBSCRIBE METAFONT <Your name>
SET METAFONT MAIL ACK
```

The address of the list is `metafont@ens.fr` (at the notorious Ecole Normale Superieure de Paris). Owner of the list is Jacques Beigbeder (`beig@ens.fr`), coordinator is Yannis Haralambous (`yannis@gat.citilille.fr`). Language of the list is English; intelligent mottos are encouraged.

8 Conclusion

METAFONT, like TEX and many another 'portable' program of any complexity, merits the warning: '*Watch out for the first step*'.

I hope that a document like this may help to prevent domestic accidents involving METAFONT, and so contribute to making the task of using and designing meta-fonts an enjoyable one. My brief experience with METAFONT suggests that it can be so.

All the Best!

TEX zonder omhaal voor Atari ST en andere PC's

Robert Best

best@zeus.rijnh.nl

Abstract

Deze cursus is een vervolg op die in MAPS 93.1. Na een inleiding in het eerste hoofdstuk werden toen in de volgende hoofdstukken behandeld: Boxen, Metafont en PostScript, Figuren en een vreemd alfabet, en tot slot INITEX en INIMF.
In deze bijdrage vervolgen we met hoofdstuk 6: het maken van een mooie brief, niet via 'boxen' in TEX maar m.b.v. LATEX. In hoofdstuk 7 bekijken we de 'artikel-stijl', waarschijnlijk de meest gebruikte vorm van TEX. Dat leidt tot een vergelijking van TEX en LATEX. En tot een alternatief: TEXsis.
Deze cursus is een herdruk van een serie artikelen in het blad ST[1], uitgegeven door Stichting ST[2].
Daar zijn de in de tekst genoemde schijfjes te verkrijgen.

6 De brief, LATEX en TEX-NL

Het maken van een mooie brief is een populaire toepassing van TEX. In MAPS 93.1 pag. 60 ev, hebben we dat gedaan (Boxen) maar dat is niet echt makkelijk. We kijken eens hoe het gaat met LATEX. Dat laat wel te wensen over. Gelukkig helpt de Nederlandstalige TEX Gebruikersgroep.

6.1 Lamport format

LATEX is TEX met het format van Leslie Lamport. Om LATEX te installeren moeten we dat format aanmaken met INITEX.

In MAPS 93.1 op pag. 68 is beschreven hoe dat gaat, maar helaas onvolledig. I.p.v.: *'Zet bij elkaar op een werkschijf'* had er moeten staan: *'Maak een folder TEX op een werkschijf en zet daar in'*.

De folder TFM moet dus in een folder TEX staan die zelf niet in een folder staat, anders kan INITEX de TFM-bestanden niet vinden.

Om het LATEX format te maken moeten we PLAIN.TEX vervangen door LPLAIN.TEX, dat ook te vinden is in TEX31.LZH op disk B 98. Wis 35 regels voor het eind van LPLAIN.TEX de % voor `\input hyphen`. Zet verder LATEX.TEX en LFONTS.TEX bij INITEX.TTP en voeg de volgende 10 TFM-bestanden toe aan de 16 die er al staan: LASY5, LASY7, LASY10, CMTI7, CMSS10, CMCSC10, LINE10, LINEW10, LCIRCLE1 en LCIRCLEW. Start INITEX en tik

```
lplain \dump
```

Dat geeft LPLAIN.FMT als er voldoende ruimte op de werkschijf is. Op een 720 kb disk is de ruimte onvoldoende. Tik dan alleen `lplain`, wacht tot er een * op het scherm komt, vervang de disk door een lege en tik dan pas `\dump`.

Lamport heeft 4 'documentstijlen' ontworpen: brief, artikel, rapport en boek. Hier bekijken we alleen de brief.

6.2 De brief

Een LATEX-brief ziet er als volgt uit:

```
\documentstyle{letter}
\address{A. Texnicus \\
  Tolstr.\ 88, \\
  1234 TT Assen}
\signature{Alex}
\begin{document}
\begin{letter}{P. Puk \\
  Pompoen 11 \\
  8888 PP Peek}
\opening{Beste Pietje,}
brieftekst brieftekst brieftekst
\closing{Groeten,}
\end{letter}
\end{document}
```

Het eerste adres komt in het briefhoofd; de geadresseerde staat na `\begin{letter}`.

Om dit TEX-bestand om te zetten in een DVI-bestand moet je het met LETTER.STY (uit STYLES.LZH op disk B 98) en LPLAIN.FMT op de TEX-werkschijf zetten. De eenvoudigste manier om te bereiken dat

[1] Uitgave: ST45 en ST46.

[2] Stichting ST, Postbus 11129, 2301 EC Leiden, tel. 071-130045. ST is een onafhankelijk tijdschrift van en voor gebruikers van Atari ST computers

LPLAIN.FMT geladen wordt i.p.v. PLAIN.FMT is natuurlijk: LPLAIN.FMT omdopen in PLAIN.FMT. Het kan ook door na het starten van TEX.TTP te tikken:

```
&lplain lbrief
```

als LBRIEF.TEX de naam van de brief-file is. Een derde manier is (zie MAPS 93.1 pag. 68 onder het kopje Taalkeuze) bovenaan LBRIEF.TEX

```
%format LaTeX
```

te zetten, maar dat werkt alleen via de shell CTEX.PRG.

6.3 Wensen

Hoe pas je nu de standaard LATEX-brief aan aan je eigen wensen? Aan sommige wensen is tegemoet gekomen. Als je het 10 punts font te klein vindt, kan je

```
\documentstyle[12pt]{letter}
```

in de brief zetten. 11 punt kan ook, maar meer keus is er niet. Het TEX-commando `\magnification` werkt niet in LATEX.

De LATEX brief voldoet aan de normen in het land van Leslie Lamport, maar past niet ineen vensterenvelop van V&D hier; het adres staat links. Om het rechts te zetten moet LETTER.STY veranderd worden, maar dat is een gecompliceerd programma van LATEX commando's. Er is documentatie bij, LETTER.DOC, maar die is ongenietbaar voor een LATEX beginner (zoals ik). Met het LATEX handboek (zie onder Literatuur) kom je hier ook niet snel uit. Veranderen of herschrijven van een LATEX-style is een zaak voor experts. Gelukkig heeft een Nederlandse TEXpert dat gedaan.

6.4 BRIEF.STY

Op PD disk B 119 staat BRIEF.STY ontwikkeld door Victor Eijkhout. Vervang LETTER.STY door BRIEF.STY op de werkschijf. In BRIEF.STY wordt het ongebruikelijke `cmssq8` font aangeroepen. Ik heb dat vervangen door `cmbx7`. (Als je toch BRIEF.STY in de editor hebt, verwijder dan de overbodige spaties aan de regeleinden. TEMPUS doet dat razendsnel met Zeichenredundanz in het menu Text. Het bestand slinkt tot minder dan de helft!).

Zet na `\documentstyle` in LBRIEF.TEX

```
[12pt,adresrechts]{brief}
```

en laat TEX.TTP en DVI_VIEW.TTP nog eens lopen. Dat levert het gewenste resultaat als je de benodigde fonts hebt, maar dat mag nu geen probleem meer zijn. Op B 119 staat ook de voorbeeldbrief BRIEF.TEX met zeer leesbaar commentaar BRIEFDOC.TEX waarmee je de brief verder kunt aanpassen. De Engelse commando's kunnen door Nederlandse vervangen worden.

WG 13

Werkgroep 13
de De Facto Standaard
in Nederlandse TEXpertise

Toernooiveld 5, • 6525 ED Nijmegen

Werkgroep 13
Nederlandse TEX groep
Nederland

Uw brief van	Ons kenmerk	Datum
13 januari 1988	VE-NTG 002	8 october 1989

Onderwerp: nieuwe briefstijl

Hallo volkjes,

Dit is een test om te zien hoe ver ik gevorderd ben met het autentieke Nederlandse briefontwerp. Het zal waarschijnlijk nog wel een tijdje duren voor er echt iets moois uitkomt. Sprak hij bescheiden. Dit is een test om te zien hoe ver ik gevorderd ben met het autentieke Nederlandse briefontwerp. Het zal waarschijnlijk nog wel een tijdje duren voor er echt iets moois uitkomt. Sprak hij bescheiden.

Hoogachtend,
Werkgroep 13

Victor Eijkhout
coördinator

Bijlagen: De broncode van deze brief

cc: Stichting 'de Kettingbrief'

PS: panta rei

fax:	telefoon:	telefoon privé:
12345 abc	080-613169	080-448664

Figuur 1: *De brief van Victor Eijkhout*

6.5 TEX-NL

Het ontwikkelen van BRIEF.STY is een activiteit van de NTG, de Nederlandstalige TEX Gebruikersgroep. Het lidmaatschap kost f 75.– per jaar, maar dan heb je ook toegang tot een club met veel expertise in TEX. De NTG beheert de discussielijst TEX-NL die de mogelijkheid biedt om snel vragen beantwoord te krijgen, en de gelijknamige fileserver met TEX-bestanden. (Discussielijsten en fileservers maken deel uit van Internet, het wereldwijde computernetwerk.) Voor wie niet op Internet aangesloten is, is er het NTG bulletin-board FGBBS dat kosteloos toegankelijk is voor iedereen, tel. 085-217041.

De NTG organiseert cursussen en geeft rapporten uit ('MAPS'). Het adres van de NTG is:
Postbus 394, 1740 AJ Schagen.

6.6 Tip

Als je printer geen goede afdruk maakt van DVI-files, experimenteer dan eens met de blacker-waarde. In ATARI.MF staan per printer waarden voor blacker, fillin, enz. Verander blacker voor de betreffende printer en maak een nieuwe PLAIN.BSE met INIMF (zoals beschreven in MAPS 93.1 pag. 68). Maak vervolgens nieuwe printer-fonts aan met METAFONT.

6.7 Literatuur

Leslie Lamport, LATEX, *A Document Preparation System, User's Guide and Reference Manual* (Addison-Wesley).

– – * – –

7 LATEX artikel; TEXsis

Na de LATEX-brief uit het vorige hoofdstuk gaan we de artikel-stijl bekijken, waarschijnlijk de meest gebruikte vorm van TEX. Dat leidt tot een vergelijking van TEX en LATEX. En tot een alternatief: TEXsis.

7.1 Het artikel

Om een LATEX-artikel te kunnen maken moeten (i.p.v. de brief-) de artikelstijlen uit STYLES.LZH op disk B 98 gehaald worden. Dat zijn ARTICLE.STY en ART12.STY (en eventueel ART10 of ART11 als je 10 of 11 punts letters wilt).

Een LATEX-artikel ziet er als volgt uit:

```
\documentstyle[12pt]{article}

\author{A. Texnicus}
\title{\TeX\ versus \LaTeX}
\begin{document}
\maketitle

\begin{abstract}
In dit artikel worden (plain) ...
\end{abstract}

\section{De overeenkomsten}
\TeX\ en \LaTeX\ hebben ...

\section{De verschillen}
De verzameling commando's ...

\section{Conclusie}
\TeX\ en \LaTeX\ verhouden ...

\end{document}
```

Met weinig commando's is zo een keurig artikel te zetten met automatisch genummerde paragrafen (sections). Met `\subsection{}` en `\subsubsection{}` is de indeling verder te verfijnen. De nummering is hiërarchisch, b.v.

2 De verschillen

2.1 Flexibiliteit

2.1.1 Fonts

Ook wiskundige formules, literatuurverwijzingen, voetnoten, tabellen en figuren worden automatisch genummerd. Dat is handig als je later een paragraaf, formule enz. tussenvoegt. Als je de paragraaf **Fonts** van een label hebt voorzien met

```
\subsubsection{Fonts} \label{fns}
```

dan kan je elders in de tekst toch, zonder het paragraafnummer te weten, verwijzen naar deze paragraaf met `\ref{fns}`. LATEX vult dan het nummer 2.1.1 in. Dat werkt ook bij formules enz.

Met `\tableofcontents` wordt automatisch een inhoudsopgave met bladzijdenummers gegenereerd. `\listoffigures` en `\listoftables` leveren lijsten met figuren en tabellen. Voor al deze nummering moet TEX.TTP twee maal het bestand doorlopen: éénmaal om nummers aan de paragrafen, formules, bladzijden enz. te geven en in een hulpbestand te noteren, en nog een keer om de nummers in te vullen in de referenties, inhoudsopgave en lijsten.

TEX versus LATEX

A. Texnicus

October 12, 1993

Abstract

In dit artikel worden (plain) TEX en LATEX vergeleken. Wat is hun achtergrondfilosofie?

1 De overeenkomsten

TEX en LATEX hebben dezelfde basis. Dat blijkt bij het zetten van alinea's. Alinea's worden gescheiden door een lege regel.

2 De verschillen

De verzameling commando's van TEX is zeer groot. De commando-set ten dienste van de LATEX gebruiker is daarentegen beperkt gehouden.

2.1 Flexibiliteit

TEX laat de gebruiker een zeer grote vrijheid in tekstopmaak. LATEX beperkt zich tot enkele document-typen.

3 Conclusie

TEX en LATEX verhouden zich als racewagen tot familiesedan.

1

Figuur 2: *Een kort LATEX-artikel*

7.2 TEX of LATEX?

Het is niet zo dat LATEX aan TEX een aantal nuttige zaken zonder meer toevoegt. Lamport heeft de ca 900 TEX-commando's deels gehandhaafd, deels veranderd en deels verwijderd.

We hebben al gezien dat magnification niet meer werkt. De opties [11pt] en [12pt] zijn wel makkelijk, maar ze vervangen magnification maar zeer ten dele.

Macro's maken gaat niet meer met `def` maar nu met `newcommand`, b.v.

```
\newcommand {\3}{\ss}
```

De instelling van de teksthoogte is moeilijker dan in TEX. In plaats van een simpel `vsize`-commando moet je nu b.v. tikken

```
\addtolength{\topmargin}{-30pt}
\addtolength{\textheight}{60pt}
```

De regellengte is niet te veranderen, hsize werkt niet. Het commando `\vskip 50 mm` is vervangen door `\vspace{50 mm}`, en dat werkt anders, namelijk pas aan het eind van de regel.
Hetzelfde geldt voor `bigskip` enz.

Overstappen van TEX naar LATEX of terug is wel wennen: veel zaken gaan net een beetje anders. Lamport zegt zelf in zijn LATEX-boek in appendix D dat de meeste plain-TEX commando's werken, maar dat er geen gemakkelijke manier is om uit te vinden of ze moeilijkheden veroorzaken, anders dan door het te proberen. Alles wat met tabellen en outputroutines te maken heeft is veranderd.

Typerend voor LATEX is dat je niet moet proberen in te grijpen in de outputroutine, zoals we in MAPS 93.1 pag. 62 gedaan hebben, om de tekst naar eigen behoefte of smaak op te maken. Als je niet tevreden bent met de gegeven documentstijlen en hun opties, dan moet je er zelf maar één schrijven, maar dat vereist veel studie. De filosofie achter LATEX is dat een goede opmaak vakwerk is, dus dat de tekstschrijver zich moet beperken tot de tekst.

TEX en LATEX zijn bedoeld voor verschillende gebruikers. LATEX is vaak makkelijker dan TEX, maar veel minder flexibel. Een LATEX-stijl is een kant-en-klaar maaltijd, met TEX kook je zelf. Als je (met mij) van mening bent dat de schrijver wel kan beoordelen welke opmaak de leesbaarheid het beste dient, vergeet dan LATEX en neem TEX. Of TEXsis, zie volgende paragraaf. Het resultaat is des te meer bevredigend, al strookt het misschien niet helemaal met de opvattingen van sommige grafische deskundologen . . .

7.3 TEXsis

TEXsis is een macro-pakket dat evenals LATEX nuttige zaken zoals automatische nummering toevoegt, maar TEX onaangetast laat. Het is geschreven door de Amerikanen Eric Myers en Frank Paige. Het hele pakket staat op PD disk B 182, verpakt als ZIP-bestand. Uitpakken gaat comfortabel met STZIP.PRG van disk A 545.

Het format voor TEXsis wordt als volgt gemaakt. Maak een folder TEX op een werkschijf en zet daarin INITEX.TTP, PLAIN.TEX, HYPHEN.TEX, TEX.POO, de folder TFM met de 16 standaardfonts en CMSS10.TFM, TEXSIS .TEX en de 20 files met extensie .TEX uit het TEXsis-pakket waarvan de naam met TXS begint. (Om dit allemaal op een 720 kb disk te krijgen moet je wat commentaar verwijderen.) Start INITEX en tik `texsis`. Als het sterretje verschijnt, (schijf verwisselen en) `\dump` tikken. Dat levert TEXSIS.FMT waarin PLAIN.FMT opgenomen is.

Alle TEX-commando's werken dus gewoon. En extra heb je dezelfde faciliteiten voor indeling, automatische nummering en inhoudsopgave enz. als voor LATEX genoemd zijn, en nog een heleboel meer.

Een TEXsis-artikel maak je als volgt:

```
\magnification 1200
\title
  Alles over \TeXsis
\endtitle
\author
  A. Texnicus
\endauthor
\abstract
  \TeXsis\ is een verzameling ...
\endabstract
\section{Overzicht}
  Dit artikel verklaart hoe ...

\bye
```

Er is een ruledtable commando om, veel gemakkelijker dan in TEX, een tabel met omlijsting te zetten:

```
\ruledtable
Jaar      | Wereldbevolking \cr
8000 B.C. | ~~~5000000 \nr
~~50 A.D. | ~200000000 \nr
1650 A.D. | ~500000000 \nr
1850 A.D. | 1000000000 \nr
1940 A.D. | 2000000000 \nr
1990 A.D. | 5000000000
\endruledtable
```

levert:

Jaar	Wereldbevolking
8000 B.C.	5000000
50 A.D.	200000000
1650 A.D.	500000000
1850 A.D.	1000000000
1940 A.D.	2000000000
1990 A.D.	5000000000

`\cr` aan het eind van een tabelregel zet een horizontale scheidingslijn, `\nr` (norule) zet geen lijn. Zie paragraaf 7.3 van de handleiding voor meer ingewikkelde tabellen.

De handleiding bij TEXsis is geen duur boek. Hij zit er bij: MANUAL.TEX en een serie DOC-files.
MANUAL.DVI staat ook op B 182. TEXsis is vooral bedoeld voor natuurkundigen om artikelen te zetten voor hun vakbladen. Maar je kunt de fysisch-specialistische delen van de handleiding gewoon overslaan. TEXsis zelf is ook 'modulair' opgebouwd: je kunt delen weglaten of apart gebruiken. Eén van de TEXsis-macro's, TXSDCOL.TEX, is ook in (plain) TEX te gebruiken om tekst in dubbelkolom te zetten. De in MAPS 93.1 pag. 61, besproken twee-kolom routine was daar uit gedestilleerd. TXSDCOL doet meer en verdeelt de tekst op de laatste bladzijde (als die niet vol is) over twee even lange kolommen.