



macro_select.pql

by *Pequel*

sample@youraddress.com

Select() Macro Example Script

2.2

Table of Contents

Select() Macro Example Script

SCRIPT NAME	1
DESCRIPTION	1
1. PROCESS DETAILS	1
1.1 PRODUCT_CODE	1
1.2 COST_PRICE	1
1.3 DESCRIPTION	1
1.4 SALES_CODE	1
1.5 SALES_PRICE	1
1.6 SALES_QTY	1
1.7 SALES_DATE	1
1.8 LOCATION	1
1.9 MARKUP_PC	1
Derived Field Evaluation	1
1.10 MARKUP_PRICE	1
Derived Field Evaluation	1
2. CONFIGURATION SETTINGS	3
2.1 pequeldoc	3
2.2 detail	3
2.3 script_name	3
2.4 header	3
2.5 optimize	3
2.6 transfer	3
2.7 doc_title	3
2.8 doc_email	3
2.9 doc_version	3
3. TABLES	4
4. TABLE INFORMATION SUMMARY	5
4.1 Table List Sorted By Table Name	5
5. MACRO_SELECT.PQL	6
options	6
description	6
input section	6
6. PEQUEL GENERATED PROGRAM	7
7. ABOUT PEQUEL	8
COPYRIGHT	8

SCRIPT NAME

macro_select.pql

DESCRIPTION

Demonstrate the use of the &select() macro. The arguments for the &select() macro consist of a list of condition-value pairs and a final 'default' value.

1. PROCESS DETAILS

Input records are read from standard input. The input record contains **8** fields. Fields are delimited by the '|' character.

Output records are written to standard output. The output record contains **10** fields. Fields are delimited by the '|' character.

1.1 PRODUCT_CODE

Input Field

1.2 COST_PRICE

Input Field

1.3 DESCRIPTION

Input Field

1.4 SALES_CODE

Input Field

1.5 SALES_PRICE

Input Field

1.6 SALES_QTY

Input Field

1.7 SALES_DATE

Input Field

1.8 LOCATION

Input Field

1.9 MARKUP_PC

Input Derived Field

Derived Field Evaluation

```
=> &select \  
( \  
  LOCATION eq 'NSW', 0.05, \  
  LOCATION eq 'VIC', 0.045, \  
  0.035 \  
)
```

1.10 MARKUP_PRICE

Input Derived Field

Derived Field Evaluation

=> SALES_PRICE * MARKUP_PC

2. CONFIGURATION SETTINGS

2.1 *pequeldoc*

generate pod / pdf pequel script Reference Guide.: pdf

2.2 *detail*

Include Pequel Generated Program chapter in Pequeldoc: 1

2.3 *script_name*

script filename: macro_select.pql

2.4 *header*

write header record to output.: 1

2.5 *optimize*

optimize generated code.: 1

2.6 *transfer*

Copy input (including calculated fields) to output.: 1

2.7 *doc_title*

document title.: Select() Macro Example Script

2.8 *doc_email*

document email entry.: sample@youraddress.com

2.9 *doc_version*

document version for pequel script.: 2.2

3. TABLES

4. TABLE INFORMATION SUMMARY

4.1 Table List Sorted By Table Name

5. MACRO_SELECT.PQL

options

```
pequeldoc(pdf)
detail(1)
script_name(macro_select.pql)
header(1)
optimize(1)
transfer(1)
doc_title(Select() Macro Example Script)
doc_email(sample@youraddress.com)
doc_version(2.2)
```

description

Demonstrate the use of the &select() macro. The arguments for the &select() macro consist of a list of condition-value pairs and a final 'default' value.

input section

```
PRODUCT_CODE
COST_PRICE
DESCRIPTION
SALES_CODE
SALES_PRICE
SALES_QTY
SALES_DATE
LOCATION
MARKUP_PC => &select \
( \
  LOCATION eq 'NSW', 0.05, \
  LOCATION eq 'VIC', 0.045, \
  0.035 \
)

MARKUP_PRICE => SALES_PRICE * MARKUP_PC
```

6. PEQUEL GENERATED PROGRAM

```
# vim: syntax=perl ts=4 sw=4
#-----
#Generated By: pequel Version 2.2-10, Build: Thursday September 15 19:10:21 BST 2005
#           : https://sourceforge.net/projects/pequel/
#Script Name : macro_select.pql
#Created On  : Tue Sep 20 14:35:32 2005
#For         :
#-----
#Options:
#pequeldoc(pdf) generate pod / pdf pequel script Reference Guide.
#detail(1) Include Pequel Generated Program chapter in Pequeldoc
#script_name(macro_select.pql) script filename
#header(1) write header record to output.
#optimize(1) optimize generated code.
#transfer(1) Copy input (including calculated fields) to output.
#doc_title(Select() Macro Example Script) document title.
#doc_email(sample@youraddress.com) document email entry.
#doc_version(2.2) document version for pequel script.
#-----
use strict;
local $\="\n"; local $,="|";
print STDERR '[macro_select.pql ' . localtime() . "] Init";
use constant VERBOSE => int 10000;
use constant LAST_ICELL => int 9;
my @I_VAL;
my @O_VAL;
use constant _I_PRODUCT_CODE    => int 0;
use constant _I_COST_PRICE      => int 1;
use constant _I_DESCRIPTION     => int 2;
use constant _I_SALES_CODE      => int 3;
use constant _I_SALES_PRICE     => int 4;
use constant _I_SALES_QTY       => int 5;
use constant _I_SALES_DATE      => int 6;
use constant _I_LOCATION        => int 7;
use constant _I_MARKUP_PC       => int 8;
use constant _I_MARKUP_PRICE    => int 9;
&PrintHeader();
print STDERR '[macro_select.pql ' . localtime() . "] Start";
use Benchmark;
my $benchmark_start = new Benchmark;
while (<STDIN>)
{
    print STDERR '[macro_select.pql ' . localtime() . "] $. records." if ($. % VERBOSE == 0);
    chomp;
    @I_VAL = split("[|]", $_);
    $I_VAL[_I_MARKUP_PC] =      $I_VAL[_I_LOCATION] eq 'NSW'
    ? 0.05
    : $I_VAL[_I_LOCATION] eq 'VIC'
    ? 0.045
    : 0.035
;
    $I_VAL[_I_MARKUP_PRICE] = $I_VAL[_I_SALES_PRICE] * $I_VAL[_I_MARKUP_PC];
    print
        @I_VAL[0..LAST_ICELL]
;
}

print STDERR '[macro_select.pql ' . localtime() . "] $. records.";
my $benchmark_end = new Benchmark;
my $benchmark_timediff = timediff($benchmark_start, $benchmark_end);
print STDERR '[macro_select.pql ' . localtime() . "] Code statistics: @{{timestr($benchmark_timediff)}}";
#-----
sub PrintHeader
{
    local $\="\n";
    local $,="|";
    print
        'PRODUCT_CODE',
        'COST_PRICE',
        'DESCRIPTION',
        'SALES_CODE',
        'SALES_PRICE',
        'SALES_QTY',
        'SALES_DATE',
        'LOCATION',
        'MARKUP_PC',
        'MARKUP_PRICE'
    ;
}
}
```

7. ABOUT PEQUEL

This document was generated by Pequel.

<https://sourceforge.net/projects/pequel/>

COPYRIGHT

Copyright ©1999-2005, Mario Gaffiero. All Rights Reserved.

'Pequel' TM Copyright ©1999-2005, Mario Gaffiero. All Rights Reserved.

This program and all its component contents is copyrighted free software by Mario Gaffiero and is released under the GNU General Public License (GPL), Version 2, a copy of which may be found at <http://www.opensource.org/licenses/gpl-license.html>

Pequel is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

Pequel is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with Pequel; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

